

**ULTRA-LOW-POWER ULTRASONIC  
SUMMIT WIND SENSOR**

Power: 3.3 - 24 VDC

Information Given:

- Wind Speed

Range: 0.5 - 60 m/s (1.12 to 134.22 mph)

Accuracy: 0.1 m/s at 10 m/s (0.22 in. at 22 mph)

Threshold: 0.5 m/s (1.12 mph)

- Wind Direction:

Range: 0- 359°

Accuracy:  $\pm 1^\circ$  RMS at 10 m/s (22.37 mph)

Measurement:

- Power Consumption

(RS485) 0.25 mA at 38,400 bauds, 1 Hz (5V)

(UART) 0.15 mA at 38,400 bauds, 1 Hz (5V)

Baudrate: 1,200 to 115,200 (8n1) bauds

Output rate: 0.1 to 10 Hz

Output units: m/s, Knots, or Km/h

Material Machined Aluminum



Easy Mount - 2xM3 lateral female

- 3xM3 base female

Sensor: Ultrasonic Transducers (4x)

Dimensions: Diameter: 70 mm (2.76 in.)  
Height: 65 mm (2.56 in.)  
Weight: 340 grams (12 oz.)

Environmental:

- IP Protection IPX8

- Temperature Range

-15/60° C (5/140° F) if no frost

Firmware Upgradable (Configurable via cable)

Data Output:

-RS485 / MODBUS RTU -Stream or Poll

-UART / I2C -Stream or Poll

-SDI12

