

ULTRASONIC PORTABLE MINI

SPECS SHEET CMI1022

Power:

Battery powered (150 hours runtime)

Wireless charging Qi

Information given:

-Wind speed

Range: 1-25m/s (2.24-56 mph)
Accuracy: 0.3 m/s at 10 m/s (0.67 mph at 22.37 mph)
Threshold: 1 m/s (2.24 mph)

-Wind direction

Range: 0 - 359°
Accuracy: ±1°

Measurement:

-Sample rate

1 Hz

-Output units

m/s, km/h, knots, mph

Data Output:

-Bluetooth

Version 5.1
Range Up to 30 meters or 98 feet (free space)

Easy mount:

Tripod mount - Female thread



Sensors:

Ultrasonic transducers (4x)

Dimensions

Diameter: 43 mm (1.69 in.)
Height: 47 mm (1.85 in.)
Weight: 78 grams (2.75 oz.)

Environmental:

IP Code

IPX8 Protection Grade

Temperature range

-15/60° C if no frost

Humidity

0/100% HR

APP Compatibility:

Marine

GARMIN

-  Calypso Instruments Sailing
-  Anemotracker Weather4D
-  Sentinel Marine Solutions
-  iRegatta
-  eStela
-  Sail Racer
-  EDO sailing instruments
-  SailGrib
-  qtVlm Navigation and Routing
-  Tactiqs

Meteo

 Weather File

Ballistics

 Strelok Pro

Display Compatibility



ULTRASONIC PORTABLE MINI

SPECS SHEET



English version 1.0
01.03.2025

Alfonso Solans Serrano 20, local 12,
Zaragoza, Spain 50014
+34 976 291 839
sales@calypsoinstruments.com

2655 S. Le Jeune Road, Ste #905
Coral Gables, Florida USA 33134
+1(786) 321-4334 /+1(786) 321-4793
sales@calypsoinstruments.com